

DECAP ROC STRIPPER-GREASE REMOVER

PRODUCT DESCRIPTION

Decap Roc is a solvent based of different surface active agents. Clear liquid.

Decap Roc is formulated to remove Roc Cure and generally all petroleum resin based treatment products on concrete and industrial floors.

INSTRUCTION FOR USE

Dilute one volume of decap Roc in two volumes of water. Apply the product using a floor scrubber or airless spray.
Allow to act 5 to 10 minutes then brush immediately with self washing machine using a red disc and simultaneous suction.
Rince the surface with Roc neutre.

Important: After removing, the surface is mat. to obtain brilliance, refer to **Roc Finish**.

TECHNICAL SPECIFICATIONS

Aspect: clear yellow liquid Density : 1 +/- 0,1 pH : 13 +/- 0,1 Biodegradability: >90% Non-flammable

PACKAGING

• 20 litres drum. The product can be stored one year in its original container, kept in a closed place and protect from frost.

COVERAGE

Approximately 20 litres for 200 m².

HEALTH AND SAFETY

Refer to our safety data sheet.

Legal note:

Owing to the different materials, substrates and differing working conditions, no guarantee in terms of result or adhesion for whatever reason and/or legal nature can be assumed by RCR Production France. Please note, the documentation of this technical data sheet can vary depending of the respective country. Note the abroad relevant product data sheet. For the rest, the most recent general terms of business of RCR Production France can be requested from us or viewed, in their most recent version, at www.rocland.eu and printed out.

We reserve the right to make changes to the product specifications.



