

# ROC FINISH

# PRODUCT DESCRIPTION

Roc finish is a very hard mono-component water-based emulsion designed to protect floors and to help in their upkeep.

Roc finish is formulated for use on concrete and paving.

## **COVERAGE**

Approximately 1 litre for 10 m2 (minimum two layers).

## **TECHNICAL SPECIFICATIONS**

Aspect: Milky white liquid Density:  $1.1 \pm 0.1$ Non-flammable pH:  $8.0 \pm 0.1$ Application temperature: 5 to 30 °C

#### **INSTRUCTION FOR USE**

• On surfaces consisting of Roc cure, strip this using Roc decap.

• On surfaces free of any treatment (curing products, wax or similar), neutralised using **Roc neutre**, apply one coat of **Roc finish** using an application sleeve or airless spray;

Wait for this coat to dry completely before applying a second layer for a satin finish.

Can be walk on after 24 hours at 20 °C Fully useable after 36 hours at 20 °C

**Roc neutre** with daily upkeep, and **Roc polish** with weekly or monthly depending on conditions are particularly adapted to make the treatment with **Roc finish** more durable.

# PACKAGING

20 litres drum.

The product can be stored one year in its original container, kept in a closed place and protect from frost.

## **HEALTH AND SAFETY**

Non dangerous good. Refer to our safety data sheet.

## Legal note:

Owing to the different materials, substrates and differing working conditions, no guarantee in terms of result or adhesion for whatever reason and/or legal nature can be assumed by RCR Production France. Please note, the documentation of this technical data sheet can vary depending of the respective country. Note the abroad relevant product data sheet. For the rest, the most recent general terms of business of RCR Production France can be requested from us or viewed, in their most recent version, at www.rocland.eu and printed out.

We reserve the right to make changes to the product specifications.

