

# **MAINTENANCE AND CLEANING**

#### **DESCRIPTION**

You are to be the owner of a surface based on concrete floor hardeners, colored or not.

Curing membrane may change the surface look. Those products may change the gloss and aspect of the surface.

In order to preserve this floor, it's greatly recommended to respect some basic recommendations.

## PROTECTION AND MAINTENANCE OF THE SURFACE

After finishing operations, the surface stays micro-porous. In order to limit the penetration of liquids and oils, facilitate the cleaning of the surface, it is greatly recommended to protect the surface with products and techniques adapted.

# Cleaning of the surface

Concrete cure done with Roc cure:

- 1 Roc Decap (stripper-grease remover)
- 2 Cleaning with **Roc Neutre** (neutralising-cleaning agent)
- 3 Roc Seal (waterproof and oil proof sealer)

# Concrete cure done with Ecocure 17:

- 1 Roc Neutre (neutralising-cleaning agent)
- 2 Roc Finish (impregnation and pore filler)

# **Daily cleaning**

- Roc Polish (waxing floor upkeep)
- Roc Neutre (neutralising-cleaning agent)

# Specific cleaning

- Roc Détachant (cleaning product)
- Roc Neutre (neutralising-cleaning agent)

### **SAW CUT JOINTS**

We recommend to fill the saw cut joints with the following products:

## **Temporary joint sealing**

• Roc Plast 55

# **Definitive joint sealing**

- Roc Joint ES 10
- Roc Joint PU 920/925

All our technical and safety data sheet are on our web site.

## Legal note:

Owing to the different materials, substrates and differing working conditions, no guarantee in terms of result or adhesion for whatever reason and/or legal nature can be assumed by RCR Production France. Please note, the documentation of this technical data sheet can vary depending of the respective country. Note the abroad relevant product data sheet. For the rest, the most recent general terms of business of RCR Production France can be requested from us or viewed, in their most recent version, at www.rocland.eu and printed out.

We reserve the right to make changes to the product specifications.

